



PCB LAYOUT

Dimension antitheses list(尺寸对照表)						
Item(项目)	A	B	W	H	W1	端子形状
Dimension(尺寸)	见左表	见左表	3.50	3.40	2.10	U型

REV ZONE		LTR		DESCRIPTION.		ECN.NO.		Date		Approval By		Date		Thirt Angle Projection		Customer No.	
1				2		3		4		5		6		7		8	

SPECIFICATIONS:
 Current Rating: 1.0 AMP
 Contact Resistance: 30mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 300V AC/minute
 Operation Temperature: -40°C to +105°C

MATERIALS:
 Contact Material: Copper Alloy
 Contact Plating: Gold or Tin over 50u" Ni
 Insulator Material: Polyester(UL94V-0)

Ordering Code

- ① Series No.: 2 3 XX 1 XX M X X 1 0
- ② Contact Plated: 0=Tin 1=Gold
- ③ Flash: 2=Gold 3u" 3=Gold 5u"
- ④ Insulator Height: 4=Gold 10u" 5=Gold 15u" 6=Gold 30u"
- ⑤ Material Type: 0=PPS 3=Nylon-66 1=PBT 4=Nylon-6T 2=LCP 5=PA46
- ⑥ Color: 1=Black
- ⑦ Number of Contacts: Single row = 01 to 50 10 Customer Request Double row = 02 to 100
- ⑧ Tail & Mounting Style:

LYCONN
 深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

Title 1. 27 单排排母 SMT 系列 / 左贴

Date	2009-10-29	Sheet	1 of 1
Drawing No.	23XX1XXMXX100	REV	A