



PCB LAYOUT

Dimension antitheses list(尺寸对照表)						
Item(项目)	A	B	W	H	W1	端子形状
Dimension(尺寸)	见左表	见左表	4.80	3.40	3.00	U型

E		Units		mm	Scale	1:1	Drawing By		Date	Date		Date		Date	
D		Tolerance Unless		Otherwise Specified		Check By		Date	Date	Date	Date	Date	Date	Date	Date
C		X		~ ± 0.25		Approval By		Date	Date	Date	Date	Date	Date	Date	Date
B		XX		~ ± 0.20		Thirt Angle Projection		Thirt Angle Projection		Thirt Angle Projection		Thirt Angle Projection		Thirt Angle Projection	
A		XXX		~ ± 0.15		Customer No.		Customer No.		Customer No.		Customer No.		Customer No.	
REV		RELEASED		ECN.NO.		Date		Date		Date		Date		Date	
ZONE		LTR		DESCRIPTION		REV		REV		REV		REV		REV	
1		2		3		4		5		6		7		8	



深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

1.27 双排排母 SMT 系列

SPECIFICATIONS:
 Current Rating: 1.0 AMP
 Contact Resistance: 30mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 300V AC/minute
 Operation Temperature: -40°C to +105°C

MATERIALS:
 Contact Material: Copper Alloy
 Contact Plating: Gold or Tin over 50u" Ni
 Insulator Material: Polyester(UL94V-0)

Ordering Code

- ① Series No.: 2 3 XX 2 XX M X X 1 0
- ② Pitth: 3=1.27mm
- ③ Insulator Height: 20=2.0mm 34=3.4mm 43=4.3mm 44=4.4mm
- ④ Dip Spacing: 1=Single row 2=Double row
- ⑤ Number of Contacts: Single row = 01 to 50 Double row = 02 to 100
- ⑥ Tial & Mounting Style: S=Strait DIP Type M=Strait SMT Type
- ⑦ Contact Plated: 0=Tin 1=Gold Flash 2=Gold 3u" 3=Gold 5u" 4=Gold 10u" 5=Gold 15u" 6=Gold 30u"
- ⑧ Material Type: 0=PSS 3=Nylon-66 1=PBT 4=Nylon-6T 2=LCP 5=PA46
- ⑨ Color: 1=Black
- ⑩ Customer Request