



**SPECIFICATIONS:**

Current rating:2.0AMP  
 Contact Resistance:30mΩ Max  
 Insulation Resistance:1000MΩ Min.at DC 500V  
 Withstand Voltage:1000VAC for one minute  
 Operating Temperature:-40 °Cto+105±C

**MATERIALS:**

Contacts Material:Phosphor Bronze  
 Flammability Rating:UL 94V-0  
 Insulator Material:30% Glass Filled PBT

P.C.B LAYOUT

E				Units	mm	Scale	2:1	Drawing By	Date	<b>LYCN</b> ® 深圳市联益电子有限公司 <a href="http://www.lyconn.com">HTTP://WWW.LYCONN.COM</a>				
D				Tolerance Unless Otherwise Specified				Check By	Date	Date	2007/11/17	Title	DIN 41612 欧式插座/90°/公座	
C				.X ~ ±0.30				Sheet	1 of 1					
B				.XX ~ ±0.25				Approval By	Date	Thirt Angle Projection		Drawing No.	LY-OSZG-396-96-001	REV
A			RELEASED	ECN.NO.	11/17-07	.XXX ~ ±0.20						File Path	M/F/MA/GCTZ/OC	A
REV	ZONE	LTR	DESCRIPTION.	ECN.NO.	Date	Angle ~ ± 3°								
	1		2		3	4	5	6	7	8				