



SPECIFICATIONS:
 Current Rating: 3.0 A
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 500V AC/minute
 Operation Temperature: -40° C to +105° C
 MATERIALS:
 Contact Material: Brass
 Contact Plating: Gold or Tin over 50u" Ni
 Insulator Material: Polyester (UL94V-0) Standard: PBT

E						Units	mm	Scale	4:1	Drawing By	Date
D						Tolerance Unless					
C						Otherwise Specified					
B						.X ~ ±0.30					
A			RELEASED		07/11-08	.XX ~ ±0.25					
REV	ZONE	LTR	DESCRIPTION.	ECN.NO.	Date	.XXX ~ ±0.20					
						Angle ~ ± 3°					
1	2	3	4	5	6	7	8				

Lycon® 深圳市联益电子有限公司
[HTTP://WWW.LYCONN.COM](http://www.lyconn.com)

Date: 2008/07/11
 Sheet: 1 of 1
 Title: 2.54筒牛90度加排针塑胶

Approval By: _____ Date: _____
 Thirt Angle Projection
 Drawing No. _____ REV _____
 File Path: M/F/MA/GCTZ/YKZ A