



SPECIFICATIONS:

Current Rating: 10.0A
 Contact Resistance: 30mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 1000V AC/minute
 Operation Temperature: -40° C to +105° C

MATERIALS:

Contact Material: Brass
 Contact Plating: Gold or Tin over 50u" Ni
 Insulator Material: Polyester (UL94V-0) Standard: PA66

E						Units	mm	Scale	4:1	Drawing By	Date
D						Tolerance Unless				Check By	Date
C						Otherwise Specified				Date	2008/07/11
B						.X	~ ±0.30			Sheet	1 of 1
A						.XX	~ ±0.25			Title	5P焊线式连接器 公座
REV	ZONE	LTR	DESCRIPTION.	ECN.NO.	Date	.XXX	~ ±0.20			Approval By	Date
						Angle	~ ± 3°			Thirt Angle Projection	Drawing No.
										File Path	M/F/MA/GCTZ/YKZ
	1										REV
											A

LYCN® 深圳市联益电子有限公司
[HTTP://WWW.LYCONN.COM](http://www.lyconn.com)

Date: 2008/07/11
 Sheet: 1 of 1
 Title: 5P焊线式连接器 公座

Thirt Angle Projection
 Drawing No.:
 File Path: M/F/MA/GCTZ/YKZ
 REV: A