



SPECIFICATIONS:

Current Rating: 3.0 A
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 500V AC/minute
 Operation Temperature: -40°C to +105°C

MATERIALS:

Contact Material: Phosphor Bronze
 Contact Plating: Selective gold on surface contact area
 Insulator Material: Polyester(UL94V-0)
 Standard: PBT

No.of Contacts	A	B	C	D	E
9	16.33	24.99	30.81	16.10	7.90
15	24.66	33.32	39.14	24.00	7.90
25	38.38	47.04	53.04	38.14	7.90
37	54.84	63.50	69.32	54.60	7.90

E						Units	mm	Scale	10:1	Drawing By	Date
D						Tolerance Unless					
C						Otherwise Specified					
B						.X ~ ±0.30					
A						.XX ~ ±0.25					
REV	ZONE	LTR	DESCRIPTION.	ECN.NO.	Date	.XXX ~ ±0.20		Approval By		Date	
	1					Angle ~ ± 3°					

LYCN® 深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

Date: 2007/12/14
 Sheet: 1 of 1
 Title: DB压线式连接器 母座

Thirt Angle Projection

Drawing No. _____
 File Path _____
 REV: A