



SPECIFICATIONS:
 Current Rating: 2.0 AMP
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 600V AC/minute
 Operation Temperature: -40°C to +105°C

MATERIALS:
 Contact Material: Brass(H59-3)
 Contact Plating: Gold or Tin over 50u" Ni
 Insulator Material: Polyester(UL94V-0)

Ordering Code

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
 137 XX X 1 3 X XXXX R 2

- ① Series No.: 137=1.778 Pitch
- ② Number of Contacts: 01 Pin~80 Pin
- ③ Dip Spacing: 1=Single row 2=Double row
- ④ Material Type: 1=PPS
- ⑤ Insulator Height: 3=3.0mm
- ⑥ Contact Plated 1=Gold flash 2=Gold 3u" 3=Gold 5u" 4=Gold 10u" 5=Gold 15u" 6=Gold 30u" 7=Tin 200u"
- ⑦ Pin Length: L=XXXX
- ⑧ Tial & Mounting Style: S=Straight DIP Type R=Right Angle DIP Type M=Straight SMT Type
- ⑨ 1=SIP Socket 2=Pin Connectors

LYCON 深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

1.778mm双头针座/90° 系列

E		Units	mm	Scale	1:1	Drawing By		Date	
D		Tolerance Unless		Otherwise Specified		Check By		Date	
C		.X ~ ±0.30				Date	2008/08/22	Sheet	1 of 1
B		.XX ~ ±0.25				Approval By		Title	1.778mm双头针座/90° 系列
A		.XXX ~ ±0.20		Angle ~ ±3°		Date		Drawing No.	ST-1778-1207-067
REV ZONE	LTR	DESCRIPTION.	ECN.NO.	Date		File Path		REV	A
1		2	3	4	5	6	7	8	