



SPECIFICATIONS:
 Voltage rating: 250V DC/AC(rms)
 Current Rating: 1.0 AMP
 Contact Resistance: 30mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 1200V AC/minute
 Operation Temperature: -20°C to +85°C
 Single Contact

MATERIALS:

Contact Material: Phosphor Bronze
 Solder Tab: Stainless Steel
 Contact Plating: Tin over 50u" Ni
 Housing: LCP(UL94V-0)



Ordering Code

①	②	③	④	⑤	⑥	⑦	⑧
FPC	L	3	XX	1	R	U	B

- ① Series No. : FPC
- ② L=Locking Type:
N=Non-locking.
- ③ Pitch:
3=2.54mm
- ④ Number of Contacts:
03 Pin~21 Pin
- ⑤ Plating Code:
1=Tin over Nickel
- ⑥ Tail & Mounting Style:
S=Stringht DIP Type
R=Right Angle Type
M=SMT Type
- ⑦ Connection Style:
D=Downside contact
U=Upside contact
V=Vertical contact
- ⑧ Color codes:
B=Black

E		Units	mm	Scale	3:1	Drawing By		Date	
D		Tolerance Unless				Check By		Date	
C		Otherwise Specified				Date		Date	
B			.X	~	±0.30	Approval By		Date	
A			.XX	~	±0.25				
REV	ZONE	LTR			.XXX	ECN.NO.	Date	Angle	~ ±3°
1									
2									
3									
4									
5									
6									
7									
8									

LYCEN 深圳市联益电子有限公司
 HTTP://WWW.LYCONN.COM

2.54FPC 卧插/黑色

Date 2008/08/01 Sheet 1 of 1 Title
 Thirt Angle Projection
 Drawing No. LY-FPC254-XX-085 REV
 File Path M/F/MA/GCTZ/FPC A